

Ludwik - liquid for washing wood

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: Ludwik - liquid for washing wood

Other means of identification:

Non-applicable

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Cleaner

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

GRUPA INCO S.A.
ul. Wspólna 25
00-519 Warszawa - Mazowieckie - Polska
Phone: +48 22 71 15 900
info.produkty@inco.pl
www.inco.pl

1.4 Emergency telephone number: +48 22 7115900 (7.30-15.30)

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

CLP Regulation (EC) No 1272/2008:

The product is not classified as hazardous according to CLP Regulation (EC) No 1272/2008.

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Hazard statements:

Non-applicable

Precautionary statements:

Non-applicable

Supplementary information:

EUH208: Contains limonene and reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one. May produce an allergic reaction.

2.3 Other hazards:

Product fails to meet PBT/vPvB criteria

The product fails to meet the criteria due to its endocrine-disrupting properties.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mixture composed of chemical products

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

| Identification | Chemical name/Classification | Concentration |
|---|---|--------------------|
| CAS: 68891-38-3 EC: 500-234-8 Index: Non-applicable REACH: 01-2119488639-16-XXXX | Alcohols, C12-14(even numbered), ethoxylated < 2.5 EO, sulfates, sodium salts⁽¹⁾ Self-classified | 1 - <3 % |
| | Regulation 1272/2008 Aquatic Chronic 3: H412; Eye Dam. 1: H318; Skin Irrit. 2: H315 - Danger | |
| CAS: 68439-50-9 EC: 931-837-8 Index: Non-applicable REACH: Non-applicable | Alcohols, C12-14, ethoxylated (7 EO)⁽¹⁾ Self-classified | 1 - <3 % |
| | Regulation 1272/2008 Acute Tox. 4: H302; Aquatic Chronic 3: H412; Eye Dam. 1: H318 - Danger | |

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

- CONTINUED ON NEXT PAGE -

Ludwik - liquid for washing wood
SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

| Identification | Chemical name/Classification | Concentration |
|---|--|-----------------------------------|
| CAS: 67-63-0 EC: 200-661-7 Index: 603-117-00-0 REACH: 01-2119457558-25-XXXX | propan-2-ol⁽¹⁾ Regulation 1272/2008 Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336 - Danger | ATP CLP00 1 - <3 % |
| CAS: 138-86-3 EC: 205-341-0 Index: 601-029-00-7 REACH: Non-applicable | Dipentene⁽¹⁾ Regulation 1272/2008 Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Flam. Liq. 3: H226; Skin Irrit. 2: H315; Skin Sens. 1: H317 - Warning | ATP CLP00 0,1 - <1 % |
| CAS: 55965-84-9 EC: Non-applicable Index: 613-167-00-5 REACH: Non-applicable | reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)⁽¹⁾ Regulation 1272/2008 Acute Tox. 2: H310+H330; Acute Tox. 3: H301; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Dam. 1: H318; Skin Corr. 1C: H314; Skin Sens. 1A: H317; EUH071 - Danger | ATP ATP13 <0,0015 % |

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Other information:

| Identification | M-factor |
|---|--------------------------|
| reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) CAS: 55965-84-9 EC: Non-applicable | Acute 100 Chronic 100 |

| Identification | Specific concentration limit |
|--|--|
| Alcohols, C12-14(even numbered), ethoxylated < 2.5 EO, sulfates, sodium salts CAS: 68891-38-3 EC: 500-234-8 | % (w/w) >=10: Eye Dam. 1 - H318 5<= % (w/w) <10: Eye Irrit. 2 - H319 |
| reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) CAS: 55965-84-9 EC: Non-applicable | % (w/w) >=0,6: Skin Corr. 1C - H314 0,06<= % (w/w) <0,6: Skin Irrit. 2 - H315 % (w/w) >=0,6: Eye Dam. 1 - H318 0,06<= % (w/w) <0,6: Eye Irrit. 2 - H319 % (w/w) >=0,0015: Skin Sens. 1A - H317 |

SECTION 4: FIRST AID MEASURES
4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

By skin contact:

This product is not classified as hazardous when in contact with the skin. However, in case of skin contact it is recommended to remove contaminated clothes and shoes, rinse the skin or if necessary shower the affected person thoroughly with cold water and neutral soap. In case of serious reaction consult a doctor.

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

Ludwik - liquid for washing wood

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, manipulation and use, but the product contains flammable substances. In the case of inflammation as a result of improper manipulation, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilled product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

See section 8.

6.2 Environmental precautions:

Avoid spillage into the aquatic environment as it contains substances potentially dangerous for this. Contain the product absorbed in hermetically sealed containers. In the case of serious spillage into the aquatic environment notify the relevant authority.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

- CONTINUED ON NEXT PAGE -

Ludwik - liquid for washing wood

SECTION 7: HANDLING AND STORAGE (continued)

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Store in a cool, dry, well-ventilated location

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

There are no occupational exposure limits for the substances contained in the product

DNEL (Workers):

| Identification | | Short exposure | | Long exposure | |
|---|------------|----------------|----------------|-----------------------|----------------|
| | | Systemic | Local | Systemic | Local |
| Alcohols, C12-14(even numbered), ethoxylated < 2.5 EO, sulfates, sodium salts CAS: 68891-38-3 EC: 500-234-8 | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 2750 mg/kg | Non-applicable |
| | Inhalation | Non-applicable | Non-applicable | 175 mg/m ³ | Non-applicable |
| propan-2-ol CAS: 67-63-0 EC: 200-661-7 | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 888 mg/kg | Non-applicable |
| | Inhalation | Non-applicable | Non-applicable | 500 mg/m ³ | Non-applicable |

DNEL (General population):

| Identification | | Short exposure | | Long exposure | |
|---|------------|----------------|----------------|----------------------|----------------|
| | | Systemic | Local | Systemic | Local |
| Alcohols, C12-14(even numbered), ethoxylated < 2.5 EO, sulfates, sodium salts CAS: 68891-38-3 EC: 500-234-8 | Oral | Non-applicable | Non-applicable | 15 mg/kg | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 1650 mg/kg | Non-applicable |
| | Inhalation | Non-applicable | Non-applicable | 52 mg/m ³ | Non-applicable |
| propan-2-ol CAS: 67-63-0 EC: 200-661-7 | Oral | Non-applicable | Non-applicable | 26 mg/kg | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 319 mg/kg | Non-applicable |
| | Inhalation | Non-applicable | Non-applicable | 89 mg/m ³ | Non-applicable |

PNEC:

| Identification | | | | |
|---|--------------|----------------|-------------------------|-------------|
| Alcohols, C12-14(even numbered), ethoxylated < 2.5 EO, sulfates, sodium salts CAS: 68891-38-3 EC: 500-234-8 | STP | 10000 mg/L | Fresh water | 0,24 mg/L |
| | Soil | 7,5 mg/kg | Marine water | 0,024 mg/L |
| | Intermittent | 0,071 mg/L | Sediment (Fresh water) | 0,917 mg/kg |
| | Oral | Non-applicable | Sediment (Marine water) | 0,092 mg/kg |
| propan-2-ol CAS: 67-63-0 EC: 200-661-7 | STP | 2251 mg/L | Fresh water | 140,9 mg/L |
| | Soil | 28 mg/kg | Marine water | 140,9 mg/L |
| | Intermittent | 140,9 mg/L | Sediment (Fresh water) | 552 mg/kg |
| | Oral | 0,16 g/kg | Sediment (Marine water) | 552 mg/kg |

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

- CONTINUED ON NEXT PAGE -

Ludwik - liquid for washing wood



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection



The use of protection equipment will be necessary if a mist forms or if the occupational exposure limits are exceeded.

C.- Specific protection for the hands

| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|--|---------------------------------------|---|--------------|--|
|  Mandatory hand protection | Protective gloves against minor risks |  | | Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN 420:2004+A1:2010 and EN ISO 374-1:2016+A1:2018 |

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.



D.- Ocular and facial protection

| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|--|---|--|---------------------------------|---|
|  Mandatory face protection | Panoramic glasses against splash/projections. |  | EN 166:2002 EN ISO 4007:2018 | Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing. |

E.- Body protection

| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|-----------|----------------------|---|-------------------|---|
| | Work clothing |  | | Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994. |
| | Anti-slip work shoes |  | EN ISO 20347:2012 | Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 20345:2012 y EN 13832-1:2007 |

F.- Additional emergency measures

| Emergency measure | Standards | Emergency measure | Standards |
|---|---|--|--|
|  Emergency shower | ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011 |  Eyewash stations | DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011 |

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

| | |
|---------------------------|-------------------------------------|
| V.O.C. (Supply): | 1,14 % weight |
| V.O.C. density at 20 °C: | 11,72 kg/m ³ (11,72 g/L) |
| Average carbon number: | 3,85 |
| Average molecular weight: | 69,36 g/mol |

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

Ludwik - liquid for washing wood

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

| | |
|--------------------------|---|
| Physical state at 20 °C: | Liquid |
| Appearance: | Fluid |
| Colour: | Orange |
| Odour: | Citric |
| Odour threshold: | Non-applicable * |

Volatility:

| | |
|--|------------------------|
| Boiling point at atmospheric pressure: | 100 °C |
| Vapour pressure at 20 °C: | 2358 Pa |
| Vapour pressure at 50 °C: | 12420,4 Pa (12,42 kPa) |
| Evaporation rate at 20 °C: | Non-applicable * |

Product description:

| | |
|--|--------------------------|
| Density at 20 °C: | 1029,6 kg/m ³ |
| Relative density at 20 °C: | 1,03 |
| Dynamic viscosity at 20 °C: | Non-applicable * |
| Kinematic viscosity at 20 °C: | Non-applicable * |
| Kinematic viscosity at 40 °C: | Non-applicable * |
| Concentration: | Non-applicable * |
| pH: | 10 |
| Vapour density at 20 °C: | Non-applicable * |
| Partition coefficient n-octanol/water 20 °C: | Non-applicable * |
| Solubility in water at 20 °C: | Non-applicable * |
| Solubility properties: | Non-applicable * |
| Decomposition temperature: | Non-applicable * |
| Melting point/freezing point: | Non-applicable * |

Flammability:

| | |
|----------------------------|------------------------|
| Flash Point: | Non Flammable (>60 °C) |
| Flammability (solid, gas): | Non-applicable * |
| Autoignition temperature: | 225 °C |
| Lower flammability limit: | Non-applicable * |
| Upper flammability limit: | Non-applicable * |

Particle characteristics:

| | |
|-----------------------------|----------------|
| Median equivalent diameter: | Non-applicable |
|-----------------------------|----------------|

9.2 Other information:

Information with regard to physical hazard classes:

| | |
|--|------------------|
| Explosive properties: | Non-applicable * |
| Oxidising properties: | Non-applicable * |
| Corrosive to metals: | Non-applicable * |
| Heat of combustion: | Non-applicable * |
| Aerosols-total percentage (by mass) of flammable components: | Non-applicable * |

Other safety characteristics:

| | |
|---------------------------|------------------|
| Surface tension at 20 °C: | Non-applicable * |
|---------------------------|------------------|

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

Ludwik - liquid for washing wood

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Refraction index: Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

| Shock and friction | Contact with air | Increase in temperature | Sunlight | Humidity |
|--------------------|------------------|-------------------------|------------|----------------|
| Not applicable | Not applicable | Precaution | Precaution | Not applicable |

10.5 Incompatible materials:

| Acids | Water | Oxidising materials | Combustible materials | Others |
|--------------------|----------------|---------------------|-----------------------|-------------------------------|
| Avoid strong acids | Not applicable | Avoid direct impact | Not applicable | Avoid alkalis or strong bases |

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Prolonged inhalation of the product is corrosive to mucous membranes and the upper respiratory tract

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for skin contact. For more information see section 3.
- Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- CONTINUED ON NEXT PAGE -

Ludwik - liquid for washing wood

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.
IARC: propan-2-ol (3)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
- Cutaneous: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with sensitising effects. For more information see section 3.

F- Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

Other information:

The mixture is not irritant to skin - the assessment with use of the bridge methods, comparison with reference formulations for which the tests were performed.

The mixture is not irritant to eyes - the assessment with use of the bridge methods, comparison with reference formulations for which the tests were performed.

Classification number

Specific toxicology information on the substances:

| Identification | Acute toxicity | | Genus |
|--|-----------------|-----------------|--------|
| | LD50 | LC50 | |
| propan-2-ol CAS: 67-63-0 EC: 200-661-7 | LD50 oral | 5280 mg/kg | Rat |
| | LD50 dermal | 12800 mg/kg | Rat |
| | LC50 inhalation | 72,6 mg/L (4 h) | Rat |
| Alcohols, C12-14, ethoxylated (7 EO) CAS: 68439-50-9 EC: 931-837-8 | LD50 oral | 1200 mg/kg | Rat |
| | LD50 dermal | Non-applicable | |
| | LC50 inhalation | Non-applicable | |
| reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) CAS: 55965-84-9 EC: Non-applicable | LD50 oral | 64 mg/kg | Rat |
| | LD50 dermal | 87,12 mg/kg | Rabbit |
| | LC50 inhalation | 0,33 mg/L (4 h) | Rat |

11.2 Information on other hazards:

Endocrine disrupting properties

The product fails to meet the criteria due to its endocrine-disrupting properties.

Other information

Non-applicable

Ludwik - liquid for washing wood

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Acute toxicity:

| Identification | | Concentration | Species | Genus |
|--|------|-------------------|---------------------------|------------|
| Alcohols, C12-14(even numbered), ethoxylated < 2.5 EO, sulfates, sodium salts CAS: 68891-38-3 EC: 500-234-8 | LC50 | 7.1 mg/L (96 h) | Danio rerio | Fish |
| | EC50 | 7.4 mg/L (48 h) | Daphnia magna | Crustacean |
| | EC50 | 27 mg/L (72 h) | Scenedesmus subspicatus | Algae |
| Alcohols, C12-14, ethoxylated (7 EO) CAS: 68439-50-9 EC: 931-837-8 | LC50 | >10 - 100 (96 h) | | Fish |
| | EC50 | >10 - 100 (48 h) | | Crustacean |
| | EC50 | >10 - 100 (72 h) | | Algae |
| propan-2-ol CAS: 67-63-0 EC: 200-661-7 | LC50 | 9640 mg/L (96 h) | Pimephales promelas | Fish |
| | EC50 | 13299 mg/L (48 h) | Daphnia magna | Crustacean |
| | EC50 | 1000 mg/L (72 h) | Scenedesmus subspicatus | Algae |
| Dipentene CAS: 138-86-3 EC: 205-341-0 | LC50 | 38.5 mg/L (96 h) | Pimephales promelas | Fish |
| | EC50 | 0.7 mg/L (48 h) | Daphnia magna | Crustacean |
| | EC50 | 1.6 mg/L (48 h) | Selenastrum capricornutum | Algae |
| reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) CAS: 55965-84-9 EC: Non-applicable | LC50 | >0.1 - 1 (96 h) | | Fish |
| | EC50 | >0.1 - 1 (48 h) | | Crustacean |
| | EC50 | >0.1 - 1 (72 h) | | Algae |

Chronic toxicity:

| Identification | | Concentration | Species | Genus |
|--|------|---------------|---------------------|------------|
| Alcohols, C12-14(even numbered), ethoxylated < 2.5 EO, sulfates, sodium salts CAS: 68891-38-3 EC: 500-234-8 | NOEC | 0.2 mg/L | Oncorhynchus mykiss | Fish |
| | NOEC | 0.27 mg/L | Daphnia magna | Crustacean |

12.2 Persistence and degradability:

| Identification | | Degradability | | Biodegradability | |
|---|----------|----------------|-----------------|------------------|--|
| | | | | | |
| Alcohols, C12-14(even numbered), ethoxylated < 2.5 EO, sulfates, sodium salts CAS: 68891-38-3 EC: 500-234-8 | BOD5 | Non-applicable | Concentration | 10.5 mg/L | |
| | COD | Non-applicable | Period | 28 days | |
| | BOD5/COD | Non-applicable | % Biodegradable | 100 % | |
| Alcohols, C12-14, ethoxylated (7 EO) CAS: 68439-50-9 EC: 931-837-8 | BOD5 | Non-applicable | Concentration | 100 mg/L | |
| | COD | Non-applicable | Period | 14 days | |
| | BOD5/COD | Non-applicable | % Biodegradable | 95 % | |

Ludwik - liquid for washing wood

SECTION 12: ECOLOGICAL INFORMATION (continued)

| Identification | Degradability | | Biodegradability | |
|--|---------------|----------------|------------------|----------|
| propan-2-ol CAS: 67-63-0 EC: 200-661-7 | BOD5 | 1,19 g O2/g | Concentration | 100 mg/L |
| | COD | 2,23 g O2/g | Period | 14 days |
| | BOD5/COD | 0,53 | % Biodegradable | 86 % |
| Dipentene CAS: 138-86-3 EC: 205-341-0 | BOD5 | Non-applicable | Concentration | 100 mg/L |
| | COD | Non-applicable | Period | 14 days |
| | BOD5/COD | Non-applicable | % Biodegradable | 69 % |

12.3 Bioaccumulative potential:

| Identification | Bioaccumulation potential | |
|--|---------------------------|------|
| propan-2-ol CAS: 67-63-0 EC: 200-661-7 | BCF | 3 |
| | Pow Log | 0.05 |
| | Potential | Low |
| Dipentene CAS: 138-86-3 EC: 205-341-0 | BCF | 660 |
| | Pow Log | 4.57 |
| | Potential | High |

12.4 Mobility in soil:

| Identification | Absorption/desorption | | Volatility | |
|--|-----------------------|---------------------|------------|---------------------------------|
| propan-2-ol CAS: 67-63-0 EC: 200-661-7 | Koc | 1.5 | Henry | 8,207E-1 Pa·m ³ /mol |
| | Conclusion | Very High | Dry soil | Yes |
| | Surface tension | 2,24E-2 N/m (25 °C) | Moist soil | Yes |
| Dipentene CAS: 138-86-3 EC: 205-341-0 | Koc | 1300 | Henry | 3242,4 Pa·m ³ /mol |
| | Conclusion | Low | Dry soil | Yes |
| | Surface tension | Non-applicable | Moist soil | Yes |

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

The product fails to meet the criteria due to its endocrine-disrupting properties.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

| Code | Description | Waste class (Regulation (EU) No 1357/2014) |
|----------|---|--|
| 20 01 30 | detergents other than those mentioned in 20 01 29 | Non dangerous |

Type of waste (Regulation (EU) No 1357/2014):

Non-applicable

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommend disposal down the drain. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

- CONTINUED ON NEXT PAGE -

Ludwik - liquid for washing wood

SECTION 14: TRANSPORT INFORMATION (continued)

With regard to ADR 2021 and RID 2021:

- 14.1 UN number or ID number:** Non-applicable
- 14.2 UN proper shipping name:** Non-applicable
- 14.3 Transport hazard class(es):** Non-applicable
- Labels: Non-applicable
- 14.4 Packing group:** Non-applicable
- 14.5 Environmental hazards:** No
- 14.6 Special precautions for user**
- Special regulations: Non-applicable
- Tunnel restriction code: Non-applicable
- Physico-Chemical properties: see section 9
- Limited quantities: Non-applicable
- 14.7 Maritime transport in bulk according to IMO instruments:** Non-applicable

Transport of dangerous goods by sea:

With regard to IMDG 39-18:

- 14.1 UN number or ID number:** Non-applicable
- 14.2 UN proper shipping name:** Non-applicable
- 14.3 Transport hazard class(es):** Non-applicable
- Labels: Non-applicable
- 14.4 Packing group:** Non-applicable
- 14.5 Marine pollutant:** No
- 14.6 Special precautions for user**
- Special regulations: Non-applicable
- EmS Codes:
- Physico-Chemical properties: see section 9
- Limited quantities: Non-applicable
- Segregation group: Non-applicable
- 14.7 Maritime transport in bulk according to IMO instruments:** Non-applicable

Transport of dangerous goods by air:

With regard to IATA/ICAO 2021:

- 14.1 UN number or ID number:** Non-applicable
- 14.2 UN proper shipping name:** Non-applicable
- 14.3 Transport hazard class(es):** Non-applicable
- Labels: Non-applicable
- 14.4 Packing group:** Non-applicable
- 14.5 Environmental hazards:** No
- 14.6 Special precautions for user**
- Physico-Chemical properties: see section 9
- 14.7 Maritime transport in bulk according to IMO instruments:** Non-applicable

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Regulation (EC) No 528/2012: contains a preservative to protect the initial properties of the treated article. Contains bronopol (INN), reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1).

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

- CONTINUED ON NEXT PAGE -

Ludwik - liquid for washing wood**SECTION 15: REGULATORY INFORMATION (continued)**

Article 95, REGULATION (EU) No 528/2012: propan-2-ol (Product-type 1, 2, 4) ; reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (Product-type 2, 4, 6, 11, 12, 13) ; bronopol (INN) (Product-type 2, 6, 11, 12, 22) REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Regulation (EC) No 648/2004 on detergents:

In accordance with this regulation the product complies with the following:

The tensoactives contained in this mixture comply with the biodegradability criteria stipulated in Regulation (EC) n°648/2004 on detergents. The information to prove this is available to the relevant authorities of the Member States and will be shown to them by direct request or the request of a detergent manufacturer.

Seveso III:

Non-applicable

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Non-applicable

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

- Regulation (EC) No 1223/2009 of the European Parliament and of the Council of 30 November 2009 on cosmetic products
- Regulation (EC) No 648/2004 of the European Parliament and of the Council of 31 March 2004 on detergents
- Commission Regulation (EC) No 907/2006 of 20 June 2006 amending Regulation (EC) No 648/2004 of the European Parliament and of the Council on detergents, in order to adapt Annexes III and VII
- Commission Regulation (EC) No 551/2009 of 25 June 2009 amending Regulation (EC) No 648/2004 of the European Parliament and of the Council on detergents, in order to adapt Annexes V and VI thereto (surfactant derogation)

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION**Legislation related to safety data sheets:**

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMMISSION REGULATION (EU) 2020/878

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Ludwik - liquid for washing wood**SECTION 16: OTHER INFORMATION (continued)**

Acute Tox. 2: H310+H330 - Fatal in contact with skin or if inhaled.
Acute Tox. 3: H301 - Toxic if swallowed.
Acute Tox. 4: H302 - Harmful if swallowed.
Aquatic Acute 1: H400 - Very toxic to aquatic life.
Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.
Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.
Eye Dam. 1: H318 - Causes serious eye damage.
Eye Irrit. 2: H319 - Causes serious eye irritation.
Flam. Liq. 2: H225 - Highly flammable liquid and vapour.
Flam. Liq. 3: H226 - Flammable liquid and vapour.
Skin Corr. 1C: H314 - Causes severe skin burns and eye damage.
Skin Irrit. 2: H315 - Causes skin irritation.
Skin Sens. 1: H317 - May cause an allergic skin reaction.
Skin Sens. 1A: H317 - May cause an allergic skin reaction.
STOT SE 3: H336 - May cause drowsiness or dizziness.

Advice related to training:

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://echa.europa.eu>
<http://eur-lex.europa.eu>

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road
IMDG: International maritime dangerous goods code
IATA: International Air Transport Association
ICAO: International Civil Aviation Organisation
COD: Chemical Oxygen Demand
BOD5: 5day biochemical oxygen demand
BCF: Bioconcentration factor
LD50: Lethal Dose 50
LC50: Lethal Concentration 50
EC50: Effective concentration 50
LogPOW: Octanolwater partition coefficient
Koc: Partition coefficient of organic carbon
UFI: unique formula identifier
IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -